

s846 SAS

Enterprise Solid-State Drives

Highlights

- MLC NAND Flash for ultra-high performance and endurance
- Best IOPS/Watt for reduced TCO
- Advanced power loss data management technology
- Self-encrypting drive conforms to TCG's Enterprise specification

Applications/Environments

- Ultra-high performance tier-0 enterprise storage
- Enterprise-class servers and high performance computing
- · Online Transaction Processing (OLTP)
- · Financial and e-commerce
- · Database analytics



2000GB and 1600GB | MLC 2.5-inch SFF | SAS 6Gb/s

HGST Enterprise Storage Experience

HGST leverages decades of proven enterprise storage expertise in Serial Attached SCSI (SAS) design, reliability, firmware, customer qualification and system integration to the s846 2.5-inch SAS solid-state drive (SSD) family. The synergistic relationship between HGST's new throughput-enhancing SSDs and traditional HDDs provides cost effective, end-to-end enterprise-class storage solutions, delivering reliability, compatibility, capacity, cost and system performance. This combination makes HGST a leading SSD/HDD provider with the experience and technology needed to meet escalating reliability, endurance and performance in the most demanding enterprise environments.

Low Latency Self-Encrypting Drives (SEDs)

One of the primary concerns for CIOs in the enterprise is data security. Encrypted data delivers an additional level of security to enterprise systems. HGST s846 Self-Encrypting Drive (SED) SAS SSDs add a new capability—AES-XTS 256 hardware-based encryption—to enterprise systems.

In addition to its world-class performance, the s846 SAS SSD provides the most reliable, longest lasting SSD solution now available for the enterprise market. Based on fourth generation HGST patented SSD controller technology, the s846 SAS SSD delivers the best performance, endurance (i.e., device lifetimes) and reliability that is unmatched in the industry.

Features and Benefits

	Feature / Function	Benefits	
Performance	SAS interface in a 2.5-inch form factor	Industry's gold standard for enterprise performance SSDs supporting servers and Tier-0 storage applications	
	MLC NAND Flash memory	Highest write performance and endurance	
	High throughput	Random transactional performance exceeds 80,000 sustained IOPS, with sustained random or sequential large block transfers up to 530MB/s	
	Power/performance efficiency	A single s846 SAS SSD replaces large numbers of enterprise HDDs while delivering superior performance and data persistence, instant backup and recovery in the event of an unplanned power failure	
Capacity	2000GB, 1600GB	More capacity in a compact form factor for less space and power	
Reliability	Secure Array of Flash Elements™ (SAFE) technology	Provides the ability to recover from NAND Flash page, block, die and chip failures, and maximizes the Mean Time Between Failure (MTBF) and Mean Time To Data Loss (MTTDL)	
	CellCare® technology	Extends the life of Flash media to deliver enterprise-class endurance through advanced signal processing and adaptive Flash management algorithms	
Encryption	Self-encrypting drive (SED)	Adds hardware-based encryption for data security and protection; compliant to TCG Enterprise specifications	



HGST Quality and Service

HGST's s846 SAS SSD family extends the company's long-standing tradition of performance and reliability leadership. A balanced combination of new and proven technologies enables high reliability and availability to customer data.

HGST drives are backed by an array of technical support and services, which may include customer and integration assistance. HGST is dedicated to providing a complete portfolio of SSD/HDD solutions to satisfy today's monumental computing needs.

Information and Technical Support www.hgst.com (main website)

www.ngst.com (main website)
www.hgst.com/partners (partner website)

North America

support_usa@hgst.com Toll Free: +1 888 426-5214, Direct: +1 408 717-8087

Asia Pacific

support_ap@hgst.com / +65 6840 9595

EMEA and UK

support_uk@hgst.com / +44 20 7133 0032

Germany

support_uk@hgst.com / +49 6929 993601

Program Support

Partners First Program: channelpartners@hgst.com

Specifications

·	
Model # / Part #	\$846E1600M2 / 0T00159 \$846E2000M2 / 0T00167
Configuration	
Interface	SAS 6Gb/s
Capacity (GB¹) at 512 bytes/sector	1600 / 2000
Form factor	2.5-inch
Flash memory technology	Multi Level Cell (MLC)
Availability	Dual Port
Performance	
Read throughput (max MB/s, sequential 64K)	530 / 530
Write throughput (max MB/s, sequential 64K)	460 / 460
Read IOPS (max IOPS, random 4K)	80,000 / 80,000
Write IOPS (max IOPS, random 4K)	63,000 / 37,000
Reliability	
MTBF ² (M hours)	2.0
Power	
Operating (max W)	12.0
Encryption	
256-bit	Yes
Endurance	
Drive writes per day for 5 years (max)	37 / 30
Lifetime PB ¹ written (max)	110 / 110
Physical	
z-height (mm)	15
Dimensions (width x depth, mm)	69.8 x 100.2
Weight (g)	< 40
Environmental	
Operating temperature	0° to 60° C

One gigabyte (GB) is equal to one billion bytes, one terabyte (TB) is equal to 1,000GB (one trillion bytes), and one petabyte (PB) is equal to 1,000TB (one quadrillion bytes) when referring to solid-state drive or hard drive capacity. Accessible capacity will vary from the stated capacity due to formatting and partitioning of the drive, the computer's operating system, and other factors.



^{© 2014} HGST, a Western Digital company, 3403 Yerba Buena Road, San Jose, CA 95135 USA. Produced in the United States 8/14. All rights reserved.

CellCare is a registered trademark, and Secure Array of Flash Elements is a trademark, of HGST, Inc. and its affiliates in the United States and/or other countries.

HGST trademarks are intended and authorized for use only in countries and jurisdictions in which HGST has obtained the rights to use, market and advertise the brand. Contact HGST for additional information. HGST shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks.

References in this publication to HGST's products, programs or services do not imply that HGST intends to make these available in all countries in which it operates.

Product specifications provided are sample specifications and do not constitute a warranty. Information is true as of the date of publication and is subject to change. Actual specifications for unique part numbers may vary.

² MTBF target is based on a sample population and is estimated by statistical measurements and acceleration algorithms under nominal operating conditions. MTBF ratings are not intended to predict an individual drive's reliability. MTBF does not constitute a warranty.