

INTELLIGENT. CONNECTED. BUSINESS-FRIENDLY.

Kodak ScanMate i1150 and i1180 Scanners



	Kodak ScanMate i1150 Scanner	Kodak ScanMate i1180 Scanner
Recommended Daily Volume	Up to 3,000 pages per day	Up to 5,000 pages per day
Throughput Speeds* (portrait, letter/A4 size, black and white/grayscale/color)	Up to 25 ppm at 200 dpi and 300 dpi	Up to 40 ppm at 200 dpi and 300 dpi
Transaction Mode ¹	40 ppm at 200 dpi and 300 dpi - first 10 pages	
Maximum Document Size	215 mm x 355.6 mm (8.5 in. x 14 in.); Long Document Mode: up to 2 meters (78.7 in.)	
Minimum Document Size	63.5 mm x 65.0 mm (2.5 in. x 2.56 in.); Minimum width: 50.8 mm (2.0 in.) when centered using visual guides	
Paper Thickness and Weight	34-413 g/m ² (9 to 110 lb.) paper	
Feeder	Up to 50 sheets (20 lb./ 80 g/m ²) paper; handles small documents such as ID cards, embossed hard cards, business cards and insurance cards	
Document Sensing	Ultrasonic multi-feed detection; Intelligent Document Protection	
Connectivity	USB 2.0 High Speed, USB 3.0 compatible	
Bundled Software	Bundled TWAIN , ISIS , and WIA Drivers; Smart Touch; Kodak Capture Pro Software Limited Edition ; Kodak Capture Pro Software Trial Edition ; (Linux SANE and TWAIN Drivers available from www.kodak.com/go/scanonlinux)	
Recommended PC Configuration	Intel Core i7 2600 , 3.4 GHz, 4 GB RAM	EMC® Captiva® Cloud Toolkit Intel Core 2 Duo , 1 GHz, 2 GB RAM
Supported Operating Systems	Windows 8 (32-bit and 64-bit); Windows 7 SP1 (32-bit); Windows XP SP3 (32-bit and 64-bit); Windows Vista SP1 (32-bit and 64-bit); Windows Server 2008 64-bit and Server 2012 64-bit; Linux: Ubuntu 12.04	
Barcode Reading	One per page: Interleaved 2 of 5, Code 3 of 9, Code 128, Codabar, UPC-A, UPC-E, EAN-13, EAN-8, PDF417	
File Format Outputs	Single and multi-page TIFF, JPEG, RTF, BMP, PDF, searchable PDF	
Optical Resolution	600 dpi	
Output Resolution	100 / 150 / 200 / 240 / 250 / 300 / 400 / 600 / 1200 dpi	
Illumination	Dual LED	
Image Sensor	CMOS Based CIS Scanner	
Image Processing	Runs on User PC	Runs in the scanner
Imaging Features	Perfect Page Scanning; Fixed Cropping; Relative Cropping; Multi-Lingual Auto Orientation; Orthogonal Rotation; Add Border; Remove Border; Intelligent Image Edge Fill; Background Color Smoothing; Automatic Brightness/Contrast; Automatic Color Balance; Round/Rectangular Hole Fill; Sharpening; Streak Filtering; Enhanced Color Adjustment; Enhanced Color Management; Automatic Color Detection; Content or File Size Based Blank Page Removal; Fixed Thresholding; iThresholding; Lone Pixel Noise Removal; Majority Rule Noise Removal; Halftone Removal; Electronic Color Dropout (R, G, or B); Predominate (1) Color Drop Out; Multiple (up to five) Color Dropout; Dual Stream; Compression (Group 4, JPEG); Image Merge	
Operator Control Panel	Color, four-line graphical LCD display with four operator control buttons	
Dimensions	Height: 246 mm (9.7 in.); Width: 330 mm (13 in.); Depth: 162 mm (6.3 in.); Weight: 3.2 kg (7 lbs.)	
Power Consumption	Off/Standby/Sleep mode: <0.5 watts; Running: <21 watts; Idle: <14 watts	
Environmental Factors	Energy Star qualified scanners; Operating temperature: 15-35° C (59-95° F); Operating humidity: -15% to 80% RH	
Acoustical Noise (operator position sound pressure level)	Off or Ready mode: <20 dB(A) Scanning: <50 dB(A)	
Electrical Requirements	100-240 V (International); 50-60 Hz	
Accessories (Optional)	Kodak A3 Size Flatbed Accessory , Kodak Legal Size Flatbed Accessory	
Software Options	Fully supported by Kodak Capture Pro Software (Group A) and Kodak Asset Management Software	
Limited Warranty	Kodak Info Input Solution Three years (Advanced Unit Replacement)	
Approvals and Product Certifications	AS/NZS CISPR 22:2009 +A1:2010; (Class B RCM mark); CAN / CSA - C22.2 No 60950-1-07 +A1:2011 (TUV C mark); Canada CSA-CISPR 22-10 / ICES-003 Issue 5 (Class B); China GB4943.1:2011; GB9254:2008 Class B (CCC S&E mark); EN55022:2010 ITE Emissions (Class B); EN55024:2010 ITE Immunity (CE mark); EN60950-1:2006 +A1,+A11,+A12 (TUV GS mark); IEC60950-1:2005 +A1; Taiwan CNS 13438:2006 (Class B); CNS 14336-1 (BSMI mark); UL 60950-1:2007 R12.11 (TUV US mark); CFR 47 Part 15 (FCC Class B); Argentina S mark	

* Throughput speeds may vary depending on your choice of driver, application software, operating system, PC and selected image processing features

¹ Transaction Mode: Scans 40 ppm for first 10 pages only - then resumes scanning at 25 ppm

Complete specifications are available at www.kodakalaris.com/go/scanmatei1150 and www.kodakalaris.com/go/scanmatei1180

To learn more:

Visit www.kodakalaris.com/go/scanmatei1150

Or www.kodakalaris.com/go/scanmatei1180

