# **D¢LL**Technologies

**Specification Sheet** 



# PowerEdge T560

A purpose-built office-friendly server, maximizing next-gen technologies with GPU options to achieve enterprise-level performance in remote or branch office locations.

## Innovate at scale with an expandable tower server for mission-critical business workloads

The Dell PowerEdge T560, powered by the 4th or 5th Generation Intel® Xeon® Scalable processors, is an enterprise-class tower server that offers advanced technologies with accelerators. It is a purpose-built server with office-friendly acoustics that maximizes next-gen technologies to achieve optimal performance in a small footprint. The Dell PowerEdge T560 is an ideal tower server for traditional corporate IT, virtualization, database and analytics, and inferencing for Al/ML, delivering robust compute performance.

#### The latest technologies for balanced performance

This all-in-one powerhouse provides ease of management and expandability for growth and performance.

- Provides additional support for database applications with expanded storage with up to 12 x 3.5-inches drives and 24 x 2.5-inches drives allowing for a mix of HDD, SAS4 SSD, and NVMe support.
- Virtualization and AI inferencing capabilities with up to two Xeon Scalable processors, doubled-bandwidth DDR5 memory, double-speed PCIe Gen5, and up to 6 GPUs.
- · Achieves enterprise-level security requirements with cyber-resilience to store, process and analyze data.

# Cyber Resilient Architecture for Zero Trust IT environment & operations

Security is integrated into every phase of the PowerEdge lifecycle, including protected supply chain and factory-to-site integrity assurance. Silicon-based root of trust anchors end-to-end boot resilience while Multi-Factor Authentication (MFA) and role-based access controls ensure trusted operations.

#### Increase efficiency and accelerate operations with an autonomous infrastructure

The Dell OpenManage™ systems management portfolio delivers a secure, efficient, and comprehensive solution for PowerEdge servers. Simplify, automate and centralize one-to-many management with the OpenManage Enterprise console and iDRAC.

#### Sustainability

From recycled materials in our products and packaging, to thoughtful, innovative options for energy efficiency, the PowerEdge portfolio is designed to make, deliver, and recycle products to help reduce the carbon footprint and lower your operation costs. We even make it easy to retire legacy systems responsibly with Dell Technologies Services

### Rest easier with Dell Technologies Services

Maximize your PowerEdge Servers with comprehensive services ranging from Consulting, to ProDeploy and ProSupport suites, Data Migration and more – available across 170 countries and backed by our 60K+ employees and partners.

### PowerEdge T560

The Dell PowerEdge T560 is designed to address enterprise-class workloads. Ideal for:

- Traditional corporate IT
- Database and Analytics
- Virtualization
- · AI/ML and inferencing

Feature	Technical Specifications
Processor	Up to two 4th Generation Intel® Xeon Scalable processor, with up to 32 cores per processor
	Up to two 5th Generation Intel® Xeon Scalable processor, with up to 28 cores per processor
Memory	16 DDR5 DIMM slots, supports RDIMM 1 TB max
•	Speeds up to 4800 MT/s on the 4th Generation Intel® Xeon Scalable processor
	Speeds up to 5200 MT/s on the 5th Generation Intel® Xeon Scalable processor
	Supports registered ECC DDR5 DIMMs only
Storage controllers	Internal PERC: fPERC H965i, fPERC H755N, fPERC H755, fPERC H355, fPERC HBA355i, HBA465i fPERC
	Internal Boot: Boot Optimized Storage Subsystem (BOSS-N1): HWRAID 2 x M.2 NVMe SSD drives, or USB
	External HBA (non-RAID): PERC HBA355e
	Software RAID: S160 (for NVMe drives only)
Drive Bays	Front bays:
	Up to 12 x 3.5-inch SAS/SATA HDD drives, max 180 TB
	Up to 8 x 3.5-inch SAS/SATA HDD drives, max 120 TB
	Up to 8 x 3.5-inch SAS/ SATA HDD + 8 x 2.5-inch NVMe SSD drives, max 240 TB
	Up to 8 x 2.5-inch SAS/SATA HDD drives, max 120 TB
	Up to 16 x 2.5-inch SAS/SATA HDD drives, max 240 TB
	Up to 24 x 2.5-inch SAS/SATA HDD drives, max 360 TB
Power Supplies	600 W Platinum 100-240 VAC/240 VDC
	700 W Titanium 200-240 VAC/240 VDC
	800 W Platinum 100-240 VAC/240 VDC
	• 1100 W Titanium 100-240 VAC/240 VDC
	• 1100 W DC/-48-(-60) V
	• 1400 W Platinum 100-240 VAC/240 VDC
	1400 W Titanium 100-240 VAC/240 VDC
	1400 W Titanium 277 VAC/336 VDC
	1800 W Titanium 200-240 VAC/240 VDC
	2400 W Platinum 100-240 VAC/240 VDC
	2800 W Titanium 200-240 VAC/240 VDC
Cooling Options	Air cooling
Fans	Up to eight Standard (STD) fans or High performance (HPR) fans
Dimensions	Height — 464.0 mm (18.26 inches) (with feet)
	508.8 mm (20.03 inches) (with caster wheels)
	446.0 mm (17.60 inches) (without feet)
	• Width — 200.0 mm (7.87 inches)
	• Depth — 678.2 mm (26.70 inches) (with bezel)
	660.6 mm (26 inches) (without bezel)
Form Factor	4.5U tower server
Embedded Management	• iDRAC9
	iDRAC Direct
	iDRAC RESTful API with Redfish
	iDRAC Service Module
	Quick Sync 2 wireless module
Bezel	Optional security bezel
OpenManage Software	OpenManage Enterprise
	OpenManage Power Manager plugin
	OpenManage Service plugin
	OpenManage Update Manager plugin
	CloudIQ for PowerEdge plug in
	OpenManage Enterprise Integration for VMware vCenter
	OpenManage Integration for Microsoft System Center
	OpenManage Integration with Windows Admin Center
Mobility	OpenManage Mobile
OpenManage Integrations	BMC Truesight
	Microsoft System Center
	OpenManage Integration with ServiceNow
	Red Hat Ansible Modules
	Terraform Providers
	VMware vCenter and vRealize Operations Manage
Security	Cryptographically signed firmware
	Data at Rest Encryption (SEDs with local or external key mgmt)
	Secure Boot
	Secure Erase
	Secured Component Verification (Hardware integrity check)
	Silicon Root of Trust
	System Lockdown (requires iDRAC9 Enterprise or Datacenter)  TRACE FIRE COLORS AND ADDRESS AND ADD
E 1 11 11 11 11 11 11 11 11 11 11 11 11	TPM 2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ
Embedded NIC	2 x 1GbE LOM on Planar
Network Options	1 x OCP x8 card 3.0
	Note: The system allows both LOM on planar and OCP card to be installed on the system.
GPU Options	Up to 2 x 300 W DW or 6 x 75 W SW

Feature	Technical Specifications		
Ports	Front Ports  1 x USB 2.0  1 x USB 3.0  1 x iDRAC Direct (Micro-AB USB) port	Rear Ports  1 x USB 2.0  1 x USB 3.0  1 x Serial port (optional)  1 x Dedicated iDRAC (RJ45) port  1 x VGA port  2 x Ethernet ports	
	Internal Ports  • 1 x USB 3.0 (optional)		
PCIe	Up to six PCle slots:  Slot 1: x16 Gen5 Full height, Full length  Slot 2: x16 Gen5 Full height, Full length  Slot 3: x16 Gen4 Full height, Half length  Slot 4: x16 Gen4 Full height, Half length  Slot 5: x16 (x8 lanes) Gen4 Full height, Half length  Slot 6: x16 Gen4 Full height, Half length		
Operating System and Hypervisors	Canonical Ubuntu Server LTS  Microsoft Windows Server with Hyper-V  Red Hat Enterprise Linux  SUSE Linux Enterprise Server  VMware ESXi		
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you.		

Discover more about PowerEdge servers

