

FIREBOX

S5800 SERIES

TOUCH TO FEEL THE DIFFERENCE OF WORLD CLASS ENGINEERING

Experience the latest in adaptive LCD design with the FireBox S5800 Series. An industry leader, the S5800 Series delivers an attractive, space saving design with the addition of stereo speakers to interface with all multi-media applications. The S5800 Series incorporates a bright, high contrast ratio 15" TFT LCD with wide viewing angles to improve image quality at various viewing angles. Available in either resistive, SAW or capacitive touch sensors which interface to a Dual touch controller.

The ability to easily integrate an MSR coupled with the stability of our mounting base makes this touch monitor a winner no matter the application.

SPECIFICATIONS:

LCD Panel	15" TFT LCD Active Matrix Display
Resolution	1024 x 768 pixels, 16.7M Colors
Contrast Ratio	500:1
Brightness	250 cd/m ²
Response Time	12 ms
Pixel Pitch	0.297 mm x 0.297 mm
Plug & Play	DDC 2B Compliance
OSD (On Screen Display)	Auto Tune, Brightness, Contrast, Clock, Phase, H-position, V-position, Recall
Touch Technology	5 Wire Resistive, SAW, Capacitive
Touch Interface	Dual (Serial/USB)
Operating Environment	0°C - 40°C (32°F - 104°F) 10%-80% (no condensation)
Storage Conditions	0°C - 40°C (32°F - 104°F) 10%-80% (no condensation)
Product Dimension (W x H x D)mm	13.97"(355mm) x 12.59"(320mm) x 7.87"(200mm)
Package Dimension (W x H x D)mm	17.71"(472mm) x 16.73"(415mm) x 11.22"(285mm)
Weight Gross	15.8 lbs (7.167 Kg)
Stand Style	U-Mount Cable Management Base
Mounting Option	Desktop Placement, VESA Mountable
Monitor Tilting Degree	160°
Color	Black
Viewing Angle	-75° / +75° / -60° / +60° (L/R/U/D)
MTBF	50,000 Hours
PC Video Interface	Analog RGB (VGA)
Horizontal Scan Rate (KHz)	30 - 60 KHz
Vertical Scan Rate (Hz)	56 - 75 KHz
Display Mode	VGA 640 x 480 (60/66/70/72/75 Hz) SVGA 800 x 600 (60/70/72/75 Hz) XGA (1024 x 768 (56/70/75 Hz)
OSD Control	Power On/Off with LED, Menu Auto Tune, Adjustment (+/-)
Built-in Speaker	2W x 2
Electrical Power	Adapter Input 100-240 VAC, 50-60Hz 1.5 A Adapter Output 12 VDC, 4.16A (C+)
Power Consumption	30W (Max)
Certification	FCC, CE, MIC, UL

- Accurate, cost effective resistive touch technology
- Attractive, slim profile increases work space
- U-Mount base ensures stable mounting system
- Nova LCD Technology provides clear and bright images under the most demanding light conditions
- ESP touch sensors delivers fast, accurate touch response
- 3 year warranty

U-MOUNT

Designed with versatility in mind, the U-Mount system provides a stable mounting system no matter the location. Standard features include 75mm VESA mount and internal cable management.

2D

Our monitors are so slim, we had to remove a dimension! Industry leading, attractive profile maximizes overall work space

ESP⁺

Delivers durable, fast and accurate touch response within < 1.5% of true position.

ESP sensors are designed to provide over 80% light transmission for improved image quality along with < 50g activation force to ensure operator accuracy.

POWER STACK SYSTEM

Adding the Power Stack System to your Firebox touch monitor allows for cost effective, seamless integration of peripheral devices such as biometric scanners and MSR's.

NOVA LCD TECHNOLOGY

High contrast ratio, high brightness and wide viewing angles are the keys to providing brilliantly clear and crisp images under the most demanding light conditions.